

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : G06K 11/08, G06F 3/033, 1/16		A1	(11) International Publication Number: WO 00/21024
			(43) International Publication Date: 13 April 2000 (13.04.00)
(21) International Application Number: PCT/US99/19598			(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
(22) International Filing Date: 26 August 1999 (26.08.99)			
(30) Priority Data: 09/167,814 7 October 1998 (07.10.98) US 09/187,903 6 November 1998 (06.11.98) US			
(71) Applicant: INTEL CORPORATION [US/US]; 2200 Mission College Boulevard, Santa Clara, CA 95052 (US).			
(72) Inventors: DUNTON, Randy; 16026 S. 14th Drive, Phoenix, AZ 85045 (US). CHARLESWORTH, Thomas; 25805 Chisum Street, Scottsdale, AZ 85255 (US). RICHARDSON, John; 2748 N.E. 19th Avenue, Portland, OR 97212 (US). SILVESTER, Kelan; 19840 N.W. Metolius Drive, Portland, OR 97229 (US). SHIMODA, Marion; 20045 S.W. Nancy Lane, Aloha, OR 97007 (US).			
(74) Agent: TROP, Timothy; Trop, Pruner, Hu & Miles, P.C., Suite 100, 8554 Katy Freeway, Houston, TX 77024 (US).			Published With international search report.

(54) Title: INPUT DEVICE USING SCANNING SENSORS



(57) Abstract

An electronic device (10) receives inputs using images of input devices (34a) and scanning sensors (14, 16, 22) that detect user interaction with those images. For example, an image of a mouse (34a) may be projected and the user's interaction with that image may be scanned using digital video cameras (14, 16, 22). These user movement images may then be analyzed to determine, for example, the direction, extent and rate of movement of the user to provide pointer position command signals. Similarly the user's movement relative to a virtual keyboard image (34b) may be analyzed and converted into key actuation signals for responding to the actuated virtual keys.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Input Device Using Scanning Sensors

Background

This invention relates generally to input devices for electronic devices including computer systems and particularly to such devices using video control inputs.

5 A variety of pointing devices have been used in computer systems to control the position of a pointer or cursor on a display. A pointer or cursor is an image that may be moved across the screen to select a particular option provided in the form of a physical depiction on a user interface. In this way, the user may interact with a video display to provide focus to particular tasks and activities offered through the user interface.

10 Known pointing devices include the mouse, track ball and the pointing stick. All of these devices generally involve an electromechanical interface which is prone to failure.

When the interface fails, it may result in an incorrect signal which may cause movement of the pointing device to be incorrectly reflected in the pointer position of the display.

15 Another well known pointing device, the touch pad pointing device, allows the user to touch a contact surface. Movements of the user's finger on the contact surface are tracked as corresponding movements of the pointer on the computer display. Normally, touch pads have capacitive sensors which detect finger position and movement and translate that movement into position control signals.

20 The touch pad pointing devices are subject to being fouled by dirt or moisture, resulting in incorrect signals as described above. In addition the touch pad devices provide a limited degree of movement, making it difficult to learn to control the pointer using the limited movements available through the pointing devices.

25 A number of computer systems use keyboards for inputting text information to the computer. The keyboard is generally connected to the computer by a cable. Like the pointing device, the keyboard involves an electromechanical interface which is prone to failure. These failures may result in the inability of a particular key to activate a particular input. In any case, inputs which are provided to the keyboard may be inaccurately reflected in the text which appears on the display screen.

30 Thus, there is a need for an improved input device which allows the user to input information in ways which may be less prone to failure.

A number of electronic devices, including computer systems, include relatively bulky input devices such as keyboards. For example, in many portable computers such as laptop or

notebook computers, a folding housing is used in which the display is essentially one portion of the overall housing and the keyboard is the other portion. Thus, a considerable portion of the overall bulk of the device is taken up by the keyboard. Similarly in some personal digital assistants (PDAs) or palm-sized computers, the keyboard or keypad input device takes up a considerable portion of the overall bulk of the device.

There is a demand for ever smaller computing devices. Portable computers such as laptop or notebook computers are progressively decreasing in size. Similarly there is increasing interest in palm-sized or PDA-type computer systems.

Thus, there is a continuing demand for new ways to reduce the size of electronic devices including computer systems.

Summary

In accordance with one embodiment, a method for inputting data to an electronic device includes projecting an image on a surface. User movements are detected relative to the projected image.

Brief Description Of The Drawings

Figure 1 is a side elevational view of one embodiment in accordance with the invention;

Figure 2 is a front elevational view of the embodiment shown in Figure 1;

Figure 3 is a top plan view of the images which may be projected by the device shown in Figure 1;

Figure 4 is a block diagram of one embodiment in accordance with the invention for implementing the device shown in Figure 1;

Figure 5 is a flow diagram of the process of forming a device which can provide the features of the device shown in Figure 1 in one embodiment in accordance with the invention;

Figure 6 is a flow diagram for one software implementation of the embodiment shown in Figure 1; and

Figures 7 and 8 are flow diagrams for calibration software in one embodiment in accordance with the invention.

Detailed Description

An electronic device which may be implemented as the computer system 10, shown in Figure 1, may include a housing 12 which includes a display 18. Unlike conventional computer systems, the system 10 may not have a keyboard or a pointing device. Scanning sensors 14 and 16 may be provided on extended arms 26 and 30 to enable scanning of the region in front of the housing 12. The scanning sensors 14 and 16 may, for example, be digital cameras that produce streaming video which is conducted through cables contained in the arms 26 and 30 to the housing 12. An additional scanning sensor 22 may be provided on the front face of the housing 12 beneath the display 18, as shown in Figure 2.

Also situated on the housing 12 is a projector 20 that projects an image onto a surface, such as a desktop, situated in front of the housing 12. The projector 20 may for example, be a liquid crystal display (LCD) projector, a laser projector or a light engine projector such as a digital light processing (DLP) light engine from Texas Instruments, Inc. The region where the image is projected may be the same region which is scanned by the scanning sensors 14, 16 and 22. Each scanner may be aligned transversely to each of the other scanners for better three dimensional imaging. The housing 12 may be supported at an angled orientation by the stand 24.

In one embodiment in accordance with the invention, one or more input devices, shown in Figure 3, such as a virtual keyboard 34a and mouse 34b may be projected onto a surface in front of the housing 12. However, the invention is not limited to this illustrated embodiment. When the user positions his or her hands over the image as the user would in using a physical input device, the scanning sensors may capture the movement of the user's hands and convert this movement into input command signals. For example, movements of the user's hand over the surface upon which the mouse image 34b was projected may be converted into pointer position signals for moving the position of the pointer on the display 18. Similarly, typing movements of the user's hands over the surface upon which the keyboard image 34a was projected may cause the corresponding textual input to be entered and to appear on the display 18. Thus, an electromechanical input device may be eliminated.

Alternatively, the scanning sensors may sense the projected light reflected from the user's hands. The scanning sensors may also detect the combination of the reflected, projected light and the user's hands. Also, the projected images may move so as to "follow" the detected movement of the user's hands.

Turning now to Figure 4, an example of a computer system 35 for implementing one embodiment in accordance with the invention may include a processor 36 coupled to a host bus 38. The illustrated computer system 35 includes the 440BX chip set with a Pentium® II processor available from Intel Corporation. The host bus 38 is coupled to a host bridge 40 which in turn couples a main memory 42. The host bridge 40 also couples an accelerated graphic port (AGP) bus 48 (see Accelerated Graphics Port Interface Specification, Revision 1.0, published on July 31, 1996, by Intel Corporation of Santa Clara, California) which couples a graphic device 50. The graphics device 50 may receive inputs from the scanning sensors 14, 16 and 22 and may display the resulting inputs on a display 18 which is also coupled to the graphics device 50. The graphics device 50 may also have a video basic input/output system (BIOS) 54 and a graphics local memory 56.

~~The host bridge 40 is also coupled to a bus 44 which may include a plurality of slots 46 for receiving peripheral devices. The bus 44 is also coupled to a bus-to-bus bridge 58 which is in turn coupled to an additional bus 70. The bus 70 includes a plurality of slots 72 for receiving additional peripheral devices and the system BIOS 74. The bridge 58 may also couple to a plurality of ports 60 and 66. The port 60 may be coupled, for example, to a hard disk drive 62 which stores one or more programs 64, 106 and 122 as indicated. The port 66 may be coupled to the projector 20.~~

While one example of a computer system is shown in Figure 4, those skilled in the art will appreciate that a number of other systems may be utilized to achieve the objectives set forth herein. Therefore it should be understood that the system illustrated is only an example.

Turning now to Figure 5, one embodiment of a method for providing the devices having the previously described functionality is illustrated in accordance with the invention. Initially a system is provided with video capability, as indicated in block 76. For example, a computer system may be provided with the ability to process a plurality of streaming video inputs. The system may also be equipped with a plurality of digital cameras. A projector is enabled to project an image of an input device on a surface, as indicated in block 78. The ability to provide video analysis of the resulting movements of the user's hands, for example, may also be provided as indicated in block 80. In accordance with one embodiment, the video analysis may be a conventional pattern recognition software which recognizes the shape of the user's hand and corresponding movements thereof. Next, the ability to convert the user's movements in association with the projected images to a pointer position control signal may

be provided, as indicated in block 82. Finally, the ability to convert the movements of the user into text inputs may be provided, as indicated in block 84. In addition, an audible confirmation, such as a key clicking sound may be produced when a keystroke is recognized.

Turning now to Figure 6, software 64 may be stored on the hard disk drive 62 in one embodiment according to the invention. Initially the software causes the image of one or more input devices to be projected onto a surface. For example, the image of a keyboard and a mouse may be projected, as indicated in block 86. Thereafter streaming video may be received (block 87) and a particular video frame may be selected, as indicated at block 88. The frame may be selected randomly, or at regular intervals, for example, using a selection technique.

In addition, a scene change detector may be used to determine when there is a significant change in scene. When a significant scene change occurs, a frame may be captured for subsequent analysis. Scene change detectors are known in the art and may involve an analysis of the pattern of intensity signals determined by the pixels that make up an imaging array in one or more cameras. For example, the various pixel sensors may provide output signals. If an output signal is above a certain intensity level, it may be considered white and if it is below a certain level it may be considered to be black. A significant change in the number of white versus black output signals can be recognized as a scene change initiating the selection of one frame from the streaming video.

While the present invention has been described with respect to the use of a single frame for this analysis, a continuing analysis can be done by successively or continually analyzing successive frames. Oversampling may be used to insure that movements are detected.

In the embodiment illustrated in Figure 6, once a frame is selected, as indicated in block 88, conventional pattern recognition software may be utilized to determine if a particular image pattern is represented by the digital video data stream, as indicated in block 92. This software may recognize a particular preprogrammed image such as the position of the user's fingers on a virtual keyboard or the position of the user's hand on top of a virtual mouse. This software may recognize the image by comparing it to a previously recorded depiction or the software may be trained to learn a particular image through cooperation of the computer owner or user, using learning software.

At diamond 94, the software checks to determine whether the selected frame contains a pattern matching a predetermined pattern which corresponds to a particular input command. If not, flow returns to select another frame.

5 If a pattern match is detected, the first and a subsequent frame are compared as indicated in block 96. Next, a check determines whether the comparison indicates a change in position (diamond 98). If so, the rate and direction of movement of the image may be determined (block 100). The rate and/or direction of movement can be used to provide corresponding command inputs. For example, in connection with the movement of the user's hand in association with the mouse image, the direction and rate of movement can be
10 reflected in corresponding movements of the pointer on the display 18. For example, a correlation factor may be used to calculate the three dimensional position of an "on screen" pointer (block 102). ~~The user inputs may be represented by a signal to the graphics device~~ 50
to move the pointer on the display 18 according to the direction or rate of movement of the user's hand (block 104). The flow cycles back to select a new frame (at block 88) to start the
15 comparison again.

Alternatively, a distinct object may be associated with the user so that the object may be easily recognized. For example, a distinctly colored ring may be used which can be readily detected. Movement of the ring may be detected as a pointer position command.

20 Software 106 for enabling the system to calibrate a focus point for pointer position commands is illustrated by Figure 7. The software 106 may be utilized during a calibration period in order to program the system to recognize the desired inputs. Referring to Figure 7, initially streaming video is received as indicated in block 108. A frame of that streaming video is captured, as illustrated in block 110.

Next, the system is prompted for movement in a defined direction as shown in block
25 112. For example, an on screen display may guide the user through the learning process. For example, the on screen display may first direct the user to show a left cursor position command. The sequence then cycles through each of the cursor command directions. Once the system knows what cursor command is being programmed, it may capture a new frame of video as indicated in block 114. The new frame and the prior frame are compared to
30 determine a difference that amounts to a given cursor command (block 116). A check at diamond 118 determines whether a focus point has been identified. In other words, the system must be able to differentiate the two frames sufficiently to be able to thereafter

recognize those differences as a particular pointer position command. If not, the process is tried again. Otherwise, the system saves off the focus point data of the identified focus point, as indicated in block 120.

Referring to Figure 8, the software 122 enables a calibration of speed and direction of pointer position commands. The focus point data determined by the software 106 is loaded at block 123. Streaming video is received as indicated at block 124 and a frame is captured as shown in block 126. A focus point is identified such as the user's finger as indicated in block 128 and a movement prompt is provided (block 130). The prompt may be a message block on the screen asking the user to implement what the user wants to use as a desired movement.

A new (subsequent) frame is captured in block 132 and compared to the frame captured in block 126, as illustrated by block 134.

The focus point movement is identified (block 136) and a direction and rate of movement are calculated as indicated in block 138. A correlation factor for x, y and z directions is used to calculate the corresponding rate and direction of movement of the screen pointer (block 140). The screen pointer is then moved as indicated in block 142. The user then may adjust the amount of pointer movement for a given movement of the user's finger, for example through inputs provided by a prompt screen, as indicated in block 144. In addition, the user may provide alternative inputs which could be received as a particular pointer position command. The user is then prompted to indicate whether the user is done in diamond 146. If not, the flow cycles and new commands may be learned as described above. Otherwise the flow is terminated and the information is saved (block 148).

The number of cameras that may be used may be subject to considerable variation. More cameras may result in better three dimensional imaging. This may allow movements in three dimensions to be recognized as input command signals. In addition, camera redundancy may be used to eliminate errors.

While the present invention has been illustrated with respect to separate cameras mounted on a computer, the cameras could be integrated into the housing of the computer system itself. In addition, while the invention has been illustrated in connection with cameras sensitive to light in a visible spectrum, infrared detecting cameras could be used as well.

By using streaming video to control input information, an electromechanical connection (which may be prone to errors or failure) may be eliminated in some embodiments. In addition, the accuracy of the inputs may be improved in some

embodiments, for example, as compared to touch pad pointing devices, because the possibility of incorrect actuation due to dirt or moisture may be eliminated.

Other input devices may be handled in the same fashion. For example, a telephone may be replaced with the projected image of a telephone. A computer microphone may be
5 activated when the handset is grasped and lifted as recognized by the scanning sensor system.

Dialing could be handled in the same fashion described previously in connection with actuation of the keyboard projected image.

The projected image may be altered to correspond to the portion of the input device the user sees with his or her hands positioned over a normal input device. This altered image
10 may be produced when the user's hands are detected as being in position over the surface that received the projected image. Moreover, the input device image may itself be modified to reflect the user's interaction with that image. For example, when finger movement
corresponds to key depression, the projected image may be altered to suggest that the virtual key has moved.

15 While the present invention has been described with respect to a limited number of embodiments, those skilled in the art will appreciate numerous modifications and variations therefrom. It is intended that the appended claims cover all such modifications and variations as fall within the true spirit and scope of the present invention.

What is claimed is:

1 1. A method for inputting data to an electronic device comprising:
2 projecting an image on a surface; and
3 detecting user movements relative to said projected image.

1 2. The method of claim 1 further including capturing a digital video image of the
2 user in association with the projected image and inputting a representation of said image to
3 the electronic device.

1 3. The method of claim 2 further including analyzing said digital video image
2 including using pattern recognition software.

1 4. The method of claim 3 further including determining a direction of movement
2 of an object depicted in said digital video image.

1 5. The method of claim 1 wherein projecting an image includes projecting on a
2 surface an image of a mouse and detecting user movements relative to said mouse image.

1 6. The method of claim 1 wherein projecting an image includes projecting the
2 image of a keyboard and detecting user movements relative to said keyboard image.

1 7. The method of claim 1 wherein projecting an image includes projecting an
2 image of an input device.

1 8. An article comprising a medium for storing instructions that cause a computer
2 to:
3 project an image on a surface; and
4 detect user movements relative to said image.

1 9. The article of claim 8 further including instructions that cause a computer to
2 analyze a digital video stream using pattern recognition software.

1 10. The article of claim 9 further including instructions that cause a computer to
2 determine a direction of movement of an object depicted in said digital video stream.

1 11. The article of claim 8 including instructions that cause a computer to project
2 an image of a mouse on a surface and detecting user movements relative to said mouse image.

1 12. The article of claim 8 including instructions that cause a computer to project
2 the image of a keyboard and detecting user movements relative to said keyboard image.

1 13. The article of claim 8 including instructions that cause a computer to project
2 the image of an input device.

1 14. A system comprising:
2 a processor;
3 a sensor coupled to said processor;
4 a projector coupled to said processor; and
5 a memory associated with said processor, said memory storing a computer
6 program that causes said processor to:
7 project an image of an input device using said projector; and
8 use said sensor to detect user movement relative to said image of an
9 input device.

1 15. The system of claim 14 including a plurality of digital video cameras.

1 16. The system of claim 14 wherein said program controls the position of a pointer
2 in response to movements of a user.



1 17. The system of claim 14 wherein said system is a computer system.

1 18. The system of claim 14 wherein said memory includes pattern recognition
2 software.

1 19. The system of claim 14 wherein said projector projects an image of a pointing
2 device.

1 20. The system of claim 14 wherein said projector projects an image of a
2 keyboard.

1/6



2/6




FIG. 3




FIG. 5

3/6




FIG. 4

4/6




FIG. 6

5/6




FIG. 7




FIG. 8

INTERNATIONAL SEARCH REPORT

Intern. al Application No
PCT/US 99/19598

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 G06K11/08 G06F3/033 G06F1/16

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 G06K G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 626 636 A (HITACHI LTD) 30 November 1994 (1994-11-30) column 5, line 18 -column 10, line 44 column 15, line 8 -column 17, line 11 figures 1-9B,12	1-14, 16-20
Y	---	15
X	EP 0 554 492 A (IBM) 11 August 1993 (1993-08-11) abstract column 4, line 18 -column 5, line 7 column 7, line 46 -column 8, line 53 figures 1-3	1-14, 16-20
A	---	15
	--- -/--	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

30 November 1999

Date of mailing of the international search report

08/12/1999

Name and mailing address of the ISA

European Patent Office, P.E. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer:

Baldan, M

INTERNATIONAL SEARCH REPORT

Information on patent family members

Internal Application No

PCT/US 99/19598

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0626636 A	30-11-1994	JP 6266498 A	22-09-1994
		JP 7084715 A	31-03-1995
		US 5436639 A	25-07-1995
EP 0554492 A	11-08-1993	DE 69204045 D	14-09-1995
		DE 69204045 T	18-04-1996
		JP 6083512 A	25-03-1994
		US 5767842 A	16-06-1998
DE 29802435 U	07-05-1998	NONE	
EP 0866419 A	23-09-1998	JP 10326148 A	08-12-1998
EP 0829799 A	18-03-1998	JP 5324181 A	07-12-1993
		JP 5324147 A	07-12-1993
		DE 571702 T	28-04-1994
		EP 0571702 A	01-12-1993

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/19598

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
------------	--	-----------------------

X	DE 298 02 435 U (SIEMENS NIXDORF INF SYST) 7 May 1998 (1998-05-07)	1-3, 6-10, 12-14, 17,18,20
---	---	-------------------------------------

A	page 2, line 18 -page 3, line 11 figure 1	
---	--	--

		4,5,11, 15,16,19
--	--	---------------------

Y	EP 0 866 419 A (TAKENAKA CORP) 23 September 1998 (1998-09-23) column 18, line 26 -column 20, line 4 figures 1-3	15
---	--	----

A		1-4, 8-10,14, 16-18
---	--	---------------------------

A	EP 0 829 799 A (TAKENAKA CORP) 18 March 1998 (1998-03-18)	1-4, 8-10, 14-18
---	--	------------------------

	column 2, line 16 -column 4, line 53 figures 1-4	
--	---	--

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER: _____**

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

